

EN131 150kg 2 SECTION ALUMINIUM COMBI LADDER (DW2)

A lightweight superior construction aluminium ladder designed and manufactured for the discerning tradesman. Certified to EN131 for trade use.

	DW2-	-9	-11	-13	-14
	Number of treads	9	11	13	14
	Ladder height (1) (m)	4.0	5.1	6.1	6.7
	Working height (1) (m)	5.3	6.4	7.4	8.0
	Ladder height (2) (m)	2.3	2.8	3.2	3.5
	Working height (2) (m)	3.6	4.1	4.5	4.8
	Ladder length (m)	2.42	2.95	3.48	3.75
	Ladder width (cm)	47.5	47.5	47.5	47.5
	Thickness (cm)	10.5	10.5	13	13
	Tread width (mm)	28	28	28	28
	Rails (mm)	25×58	25×58	30×75	30×75
	Weight (kg)	10.1	13.3	17.7	19.9



DW2 (Step Ladder)



DW2 (Extension)

KEY POINTS

- Available in four sizes 2x9 – 2x11 – 2x13 – 2x14.
- Can be used as an extension ladder or a step ladder.
- Sturdy aluminium stiles & Rigid grooved treads.
- Wide horizontal stabiliser bar fitted with rubber caps for added safety.
- Working height up to 8m.
- Anti-slip ribbed rungs & Non slip feet.
- Weather resistant straps.
- Fitted with interlocking clips to enhance safety in use and transportation.
- Maximum load 150Kg.